

## Pincés type P 4.5.



Ø 4.50 mm

MSA	Ø	Kg
03.875-060	0.60 mm	0.002
03.875-100	1.00 mm	0.002
03.875-150	1.50 mm	0.002
03.875-160	1.60 mm	0.002
03.875-200	2.00 mm	0.002
03.875-235	2.35 mm	0.002
03.875-250	2.50 mm	0.002
03.875-300	3.00 mm	0.002
03.875-400	4.00 mm	0.002

Pince de serrage type P 4.5.

## Entraîneurs.



MSA	Dimensions	Kg
03.838	40 x 16 x 12 mm	0.060

Jeu de 12 petits entraîneurs avec bloc de rangement.  
Ø 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.65, 0.70, 0.75, 0.85, 0.95 et 1.05 mm.

## Courroies pour les tours illustrés dans les pages précédentes.



MSA	Ø	Longueur	Kg
03.890-2	2 mm	1 m	0.015
03.890-3	3 mm	1 m	0.015
03.890-4	4 mm	1 m	0.015
03.890-5	5 mm	1 m	0.015
03.890-6	6 mm	1 m	0.015
03.890-7	7 mm	1 m	0.015
03.890-8	8 mm	1 m	0.015
03.890-10	10 mm	1 m	0.015
03.890-12	12 mm	1 m	0.015

Courroie en polyuréthane.



MSA	Ø	Longueur	Kg
03.891-4	4 mm	1 m	0.018
03.891-5	5 mm	1 m	0.018
03.891-6	6 mm	1 m	0.018

Courroie POLYCORD verte.